




# REXNORED BEARING LIMITED

## 85 mm x 130 mm x 22 mm SKF 7017 ACD/P4A angular contact ball bearings

Bearing No. 7017 ACD/P4A



7017 ACD/P4A Bearing 2D drawings and 3D CAD models

Size	130x85x22 mm
Bore Diameter	130 mm
Outer Diameter	85 mm
Width	22 mm
d	85 mm
D	130 mm
B	22 mm
d <sub>1</sub>	98.9 mm
d <sub>2</sub>	98.9 mm
D <sub>1</sub>	116.1 mm
r <sub>1,2</sub> - min.	1.1 mm
r <sub>3,4</sub> - min.	0.6 mm
a	36.2 mm
d <sub>a</sub> - min.	91 mm
d <sub>b</sub> - min.	91 mm
D <sub>a</sub> - max.	124 mm
D <sub>b</sub> - max.	126 mm
r <sub>a</sub> - max.	1 mm
r <sub>b</sub> - max.	0.6 mm
d <sub>n</sub>	101.9 mm
Basic dynamic load rating - C	63.7 kN
Basic static load rating - C <sub>0</sub>	62 kN
Fatigue load limit - P <sub>u</sub>	2.5 kN
Limiting speed for grease	9000 r/min



## REXNORED BEARING LIMITED

Lubrication	
Limiting speed for oil lubrication	14000 mm/min
Ball - $D_w$	14.288 mm
Ball - $z$	21
$G_{ref}$	11.7 cm <sup>3</sup>
Calculation factor - $e$	0.68
Calculation factor - $Y_2$	0.87
Calculation factor - $Y_0$	0.38
Calculation factor - $X_2$	0.41
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Preload class A - $G_A$	400 N
Preload class B - $G_B$	800 N
Preload class C - $G_C$	1600 N
Preload class D - $G_D$	3200 N
Calculation factor - $f$	1.15
Calculation factor - $f_1$	0.99
Calculation factor - $f_{2A}$	1
Calculation factor - $f_{2B}$	1.02
Calculation factor - $f_{2C}$	1.05
Calculation factor - $f_{2D}$	1.08
Calculation factor - $f_{HC}$	1
Preload class A	233 N/micron
Preload class B	304 N/micron
Preload class C	405 N/micron
Preload class D	549 N/micron



## REXNORED BEARING LIMITED

Category	Precision Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.93
EAN	7316570088908
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7   ISO P4
Material - Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	25 Degree
Preload	None
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Flush Ground	No
Inch - Metric	Metric
Other Features	Single Row   Angular Contact   High Precision
Long Description	85MM Bore; 130MM Outside Diameter; 22MM Width; Open Enclosure; ABEC 7   ISO P4 Precision; Steel Ball Material; 1 (Single) Bearings; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Ra
Category	Precision Ball Bearings
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>



## REXNORED BEARING LIMITED

Manufacturer Item Number	7017 ACD/P4A
Weight / LBS	2.037
Bore	3.346 Inch   85 Millimeter
Outside Diameter	5.118 Inch   130 Millimeter
Width	0.866 Inch   22 Millimeter
$d_1$	98.9 mm
$d_2$	98.9 mm
$D_1$	116.1 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
$d_a$ min.	91 mm
$d_b$ min.	91 mm
$D_a$ max.	124 mm
$D_b$ max.	126 mm
$r_a$ max.	1 mm
$r_b$ max.	0.6 mm
$d_n$	101.9 mm
Basic dynamic load rating C	63.7 kN
Basic static load rating $C_0$	62 kN
Fatigue load limit $P_u$	2.5 kN
Attainable speed for grease lubrication	9000 r/min
Attainable speed for oil-air lubrication	14000 r/min
Ball diameter $D_w$	14.288 mm
Number of balls z	21
Reference grease quantity $G_{ref}$	11.7 cm <sup>3</sup>
Preload class A $G_A$	400 N
Static axial stiffness, preload class A	233 N/ $\mu$ m
Preload class B $G_B$	800 N
Static axial stiffness, preload class B	304 N/ $\mu$ m



## REXNORED BEARING LIMITED

Preload class C $G_C$	1600 N
Static axial stiffness, preload class C	405 N/ $\mu$ m
Preload class D $G_D$	3200 N
Static axial stiffness, preload class D	549 N/ $\mu$ m
Calculation factor $f$	1.15
Calculation factor $f_1$	0.99
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.02
Calculation factor $f_{2C}$	1.05
Calculation factor $f_{2D}$	1.08
Calculation factor $f_{HC}$	1
Calculation factor $e$	0.68
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67
Mass bearing	0.9 kg